


POLARIS 53T



RECESSED TRIMLESS LED LINEAR LUMINAIRE



Code	Finish	Distribution	Diffuser	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
P53TIB/OS/F/0568/4K8	Black	Direct only	Opal	568	1327	12.2	108.8	4000	>80
P53TIB/OS/F/0848/4K8	Black	Direct only	Opal	848	1987	18.2	109.2	4000	>80
P53TIB/OS/F/1128/4K8	Black	Direct only	Opal	1128	2655	24.2	109.7	4000	>80
P53TIB/OS/F/1408/4K8	Black	Direct only	Opal	1408	3314	30.5	108.7	4000	>80
P53TIB/OS/F/1688/4K8	Black	Direct only	Opal	1688	3982	36.5	109.1	4000	>80
P53TIB/OS/F/1968/4K8	Black	Direct only	Opal	1968	4642	42.5	109.2	4000	>80
P53TIB/OS/F/2248/4K8	Black	Direct only	Opal	2248	5310	48.5	109.5	4000	>80
P53TIB/OS/F/2528/4K8	Black	Direct only	Opal	2528	5969	54.5	109.5	4000	>80
P53TIB/OS/F/2808/4K8	Black	Direct only	Opal	2808	6637	60.5	109.7	4000	>80
P53TIB/OS/F/3088/4K8	Black	Direct only	Opal	3088	7297	66.5	109.7	4000	>80
P53TIB/OS/F/3368/4K8	Black	Direct only	Opal	3368	7965	72.5	109.9	4000	>80
P53TIB/OS/F/3648/4K8	Black	Direct only	Opal	3648	8624	79	109.2	4000	>80
P53TIB/OS/F/3928/4K8	Black	Direct only	Opal	3928	9292	85	109.3	4000	>80

Dimensions in table above are for the back body only. For Individual luminaires, there is a 21mm plaster in trim on both ends and both sides. For Start of Run & End of Run luminaires, there is a 21mm plaster in on one end, and both sides. For Continuous luminaires, there is a 21mm plaster in trim on both sides.

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20

REVISED : 28September20203:11 pm



POLARIS 53T

RECESSED TRIMLESS LED LINEAR LUMINAIRE

Construction

- Extruded aluminium profile
- Clip-in diffuser
- European LED boards

Features

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- European control gear

Optical Options

Code	Description
N/A	Opal (Standard)
/HXP	Low Glare (See P53T low glare spec)

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K


For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Dimensions



Mounting Options

Code	Description
N/A	Recessed

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required

Continuous Options

Code	Description
C	Continuous
S	Start of run
E	End of run

Part numbers are for individual luminaires. For continuous replace 'F' in part number with 'C', 'S' or 'E'. Please specify continuous separately. ie **P53TCB/OS/F/2808/4K8**

synergy.gb.net

01992 445828

sales@synergy.gb.net

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

synergy.gb.net