

# SOMBRERO RING

## SUSPENDED OR SURFACE LUMINAIRE



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
Suspended							
<b>SOMRSB/F/0700/4K8</b>	Black	700 ø x 75 x 70	3124	29	107.7	4000K	>80
<b>SOMRSB/F/0900/4K8</b>	Black	900 ø x 75 x 70	4016	37	108.5	4000K	>80
<b>SOMRSB/F/1220/4K8</b>	Black	1220 ø x 75 x 70	5355	50	107.1	4000K	>80
<b>SOMRSB/F/1500/4K8</b>	Black	1500 ø x 75 x 70	7140	66	108.2	4000K	>80
<b>SOMRSB/F/2000/4K8</b>	Black	2000 ø x 75 x 70	8926	82	108.9	4000K	>80
<b>SOMRSB/F/3000/4K8</b>	Black	3000 ø x 75 x 70	14281	132	108.2	4000K	>80
Surface							
<b>SOMRCB/OS/F/0700/4K8</b>	Black	700 ø x 75 x 70	3124	29	107.7	4000K	>80
<b>SOMRCB/OS/F/0900/4K8</b>	Black	900 ø x 75 x 70	4016	37	108.5	4000K	>80
<b>SOMRCB/OS/F/1220/4K8</b>	Black	1220 ø x 75 x 70	5355	50	107.1	4000K	>80
<b>SOMRCB/OS/F/1500/4K8</b>	Black	1500 ø x 75 x 70	7140	66	108.2	4000K	>80
<b>SOMRCB/OS/F/2000/4K8</b>	Black	2000 ø x 75 x 70	8926	82	108.9	4000K	>80
<b>SOMRCB/OS/F/3000/4K8</b>	Black	3000 ø x 75 x 70	14281	132	108.2	4000K	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For BIM models, please contact us
- See website for Technical Data Sheet
- For versions with uplight, please contact sales

REVISED : 8 January 2021 10:30 am



# SOMBRERO RING

## SUSPENDED OR SURFACE LUMINAIRE

### Construction

- Extruded aluminium profile
- Clip-in diffuser
- Tridonic LED boards

### Features

- High efficiency LED boards
- Range of size options
- Wide-beam light distribution

### Applications

- Commercial and Business Areas
- Public buildings
- Retail
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

### Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- European control gear

### Optical Options

Code	Description
N/A	Opal (Standard)
HX	Low Glare

### CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

### Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

### Mounting Options

Code	Description
SB	Suspended (Standard)
CB	Surface Mounted
TB	Recessed with Trim
RB	Recessed Trimless

to specify different mounting methods replace SB in the code SOMR**SB** with your choice

### Finish Options

Code	Description
B	Black RAL 9005 (Standard)
W	White RAL 9016
S	Silver RAL 9006
RAL	Any RAL by request
SFX	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

### Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required