

Code	Finish	Diffuser	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
P3TIB/OS/F/0885/4K8	Black	Opal	885	2572	25.1	102.5	4000	>80
P3TIB/OS/F/1165/4K8	Black	Opal	1165	3434	33.2	103.4	4000	>80
P3TIB/OS/F/1450/4K8	Black	Opal	1450	4257	41.2	103.3	4000	>80
P3TIB/OS/F/1730/4K8	Black	Opal	1730	5151	49.8	103.4	4000	>80
P3TIB/OS/F/2015/4K8	Black	Opal	2015	6006	58.1	103.4	4000	>80
P3TIB/OS/F/2295/4K8	Black	Opal	2295	6868	66.5	103.3	4000	>80
P3TIB/OS/F/2580/4K8	Black	Opal	2580	7723	74.8	103.2	4000	>80
P3TIB/OS/F/2860/4K8	Black	Opal	2860	8585	83.1	103.3	4000	>80
P3TIB/OS/F/3145/4K8	Black	Opal	3145	9440	91.4	103.3	4000	>80
P3TIB/OS/F/3425/4K8	Black	Opal	3425	10302	100	103.0	4000	>80
P3TIB/OS/F/3710/4K8	Black	Opal	3710	11157	108.3	103.0	4000	>80
P3TIB/OS/F/3990/4K8	Black	Opal	3990	12019	116.2	103.4	4000	>80
P3TIB/OS/F/4275/4K8	Black	Opal	4275	12874	124.5	103.4	4000	>80
P3TIB/OS/F/4555/4K8	Black	Opal	4555	13736	133	103.3	4000	>80

Dimensions in table above are for the back body only. For Individual luminaires, there is a 21mm plaster in trim on both ends and both sides. For Start of Run & End of Run luminaires, there is a 21mm plaster in on one end, and both sides. For Continuous luminaires, there is a 21mm plaster in trim on both sides.

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20

POLARIS 3T

RECESSED TRIMLESS LINEAR LUMINAIRE

Construction

- Extruded aluminium profile
- Clip-in diffuser
- Tridonic LED boards
- Plaster in trim

Features

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- European control gear

Optical Options

Code	Description
/OS	Opal (Standard)
/HXP	Low Glare (See P3T low glare spec)

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K


For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Dimensions



Mounting Options

Code	Description
	Recessed only

Finish Options

Code	Description
B	Black RAL 9005 (Standard)
W	White RAL 9016
S	Silver RAL 9006
RAL	Any RAL by request
SFX	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required

Continuous Options

Code	Description
C	Continuous
S	Start of run
E	End of run

Part numbers are for individual luminaires. For continuous replace 'I' in part number with 'C', 'S' or 'E'. Please specify continuous separately. ie **P3TCB/OS/F/3990/4K8**