


POLARIS 70



LINEAR WITH 5 LIGHT EMITTING SIDES



Code	Finish	Distribution	Size (mm)	Lumens (lm)	Total System Wattage (W)	Colour Temp (°K)	CRI
P70/OS/F/0585/4K8	Opal	Direct / Indirect	585	1169	8	146.1	>80
P70/OS/F/0860/4K8	Opal	Direct / Indirect	860	1754	13	134.9	>80
P70/OS/F/1145/4K8	Opal	Direct / Indirect	1145	2339	16	146.2	>80
P70/OS/F/1425/4K8	Opal	Direct / Indirect	1425	2923	21	139.2	>80
P70/OS/F/1710/4K8	Opal	Direct / Indirect	1710	3508	26	134.9	>80
P70/OS/F/2265/4K8	Opal	Direct / Indirect	2265	4678	32	146.2	>80
P70/OS/F/2825/4K8	Opal	Direct / Indirect	2825	5847	42	139.2	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet
- IP20

REVISED : 26 July 2021 12:12 pm



POLARIS 70

LINEAR WITH 5 LIGHT EMITTING SIDES

Construction

- Aluminium base
- Opal PMMA diffuser
- Integral control gear

Features

- High efficiency LED boards
- Range of length options
- 5 light emitting sides

Applications

- Commercial and Business Areas
- Public buildings
- Retail/Leisure
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- 5 Year warranty

Optical Options

Code	Description
N/A	Opal (Standard)

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Mounting Options

Code	Description
P1/SUS/1.25M	Suspended 1.25M
P1/SUS/3.0M	Suspended 3M
/SM	Surface Mounted
/WM	Wall Mounted

For surface add /SM onto end of part number. For suspended specify the codes separately.

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required. Please note emergency versions are only available in 1145mm and longer.

Dimensions

