


# SOMBRERO RING LOW GLARE

SUSPENDED OR SURFACE LUMINAIRE



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
<b>SOMRSB/HX/F/0700/4K8</b>	Black	ø 700 x 75 x 70	3847	29	132.7	4000K	>80
<b>SOMRSB/HX/F/0900/4K8</b>	Black	ø 900 x 75 x 70	4946	37	133.7	4000K	>80
<b>SOMRSB/HX/F/1220/4K8</b>	Black	ø 1220 x 75 x 70	6595	50	131.9	4000K	>80
<b>SOMRSB/HX/F/1500/4K8</b>	Black	ø 1500 x 75 x 70	8793	66	133.2	4000K	>80
<b>SOMRSB/HX/F/2000/4K8</b>	Black	ø 2000 x 75 x 70	10992	82	134.0	4000K	>80
<b>SOMRSB/HX/F/3000/4K8</b>	Black	ø 3000 x 75 x 70	17587	132	133.2	4000K	>80
<b>SOMRCB/HX/F/0700/4K8</b>	Black	ø 700 x 75 x 70	3847	29	132.7	4000K	>80
<b>SOMRCB/HX/F/0900/4K8</b>	Black	ø 900 x 75 x 70	4946	37	133.7	4000K	>80
<b>SOMRCB/HX/F/1220/4K8</b>	Black	ø 1220 x 75 x 70	6595	50	131.9	4000K	>80
<b>SOMRCB/HX/F/1500/4K8</b>	Black	ø 1500 x 75 x 70	8793	66	133.2	4000K	>80
<b>SOMRCB/HX/F/2000/4K8</b>	Black	ø 2000 x 75 x 70	10992	82	134.0	4000K	>80
<b>SOMRCB/HX/F/3000/4K8</b>	Black	ø 3000 x 75 x 70	17587	132	133.2	4000K	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For BIM models, please contact us
- See website for Technical Data Sheet

REVISED : 8 January 2021 10:27 am



# SOMBRO RING LOW GLARE

## SUSPENDED OR SURFACE LUMINAIRE

### Construction

- Extruded aluminium profile
- Clip-in diffuser
- Tridonic LED boards

### Features

- High efficiency LED boards
- Range of size options
- Wide-beam light distribution

### Applications

- Commercial and Business Areas
- Public buildings
- Retail
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

### Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- European control gear

### Optical Options

Code	Description
<b>HX</b>	Low Glare

### CCT Options

Code	Description
<b>4K8</b>	4000K (Standard)
<b>3K8</b>	3000K

For 3000K version, replace '4K8' in part number with '3K8'

### Control Options

Code	Description
<b>D</b>	DALI
<b>S</b>	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

### Mounting Options

Code	Description
<b>SB</b>	Suspended (Standard)
<b>CB</b>	Surface Mounted

to specify different mounting methods replace SB in the code SOMR**SB** with your choice

### Finish Options

Code	Description
<b>B</b>	Black RAL 9005 (Standard)
<b>W</b>	White RAL 9016
<b>S</b>	Silver RAL 9006
<b>RAL</b>	Any RAL by request
<b>SFX</b>	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

### Emergency Options

Code	Description
<b>/EM</b>	3 hour maintained, manual test
<b>/ED</b>	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required

[synergy.gb.net](http://synergy.gb.net)

01992 445828

[sales@synergy.gb.net](mailto:sales@synergy.gb.net)

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

[synergy.gb.net](http://synergy.gb.net)