



| Code                      | Finish | Size (mm) | Control          | Emergency   | Delivered Lumens (lm) | Total System Wattage (W) | Efficacy (lm/cw) | Colour Temp (°K) | CRI |
|---------------------------|--------|-----------|------------------|-------------|-----------------------|--------------------------|------------------|------------------|-----|
| <b>AXMW/F/0850/4K8</b>    | White  | ø 110     | Fixed output     | No          | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/D/0850/4K8</b>    | White  | ø 110     | DALI / Switchdim | No          | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/F/0850/4K8/EM</b> | White  | ø 110     | Fixed output     | Manual test | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/D/0850/4K8/EM</b> | White  | ø 110     | DALI / Switchdim | Manual test | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/F/0850/4K8/ED</b> | White  | ø 110     | Fixed output     | DALI Test   | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/D/0850/4K8/ED</b> | White  | ø 110     | DALI / Switchdim | DALI Test   | 850                   | 9                        | 94.4             | 3K/4K/5K         | >80 |
| <b>AXMW/F/1200/4K8</b>    | White  | ø 190     | Fixed output     | No          | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/D/1200/4K8</b>    | White  | ø 190     | DALI / Switchdim | No          | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/F/1200/4K8/EM</b> | White  | ø 190     | Fixed output     | Manual test | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/D/1200/4K8/EM</b> | White  | ø 190     | DALI / Switchdim | Manual test | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/F/1200/4K8/ED</b> | White  | ø 190     | Fixed output     | DALI Test   | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/D/1200/4K8/ED</b> | White  | ø 190     | DALI / Switchdim | DALI Test   | 1200                  | 11                       | 109.1            | 3K/4K/5K         | >80 |
| <b>AXMW/F/2300/4K8</b>    | White  | ø 190     | Fixed output     | No          | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |
| <b>AXMW/D/2300/4K8</b>    | White  | ø 190     | DALI / Switchdim | No          | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |
| <b>AXMW/F/2300/4K8/EM</b> | White  | ø 190     | Fixed output     | Manual test | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |
| <b>AXMW/D/2300/4K8/EM</b> | White  | ø 190     | DALI / Switchdim | Manual test | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |
| <b>AXMW/F/2300/4K8/ED</b> | White  | ø 190     | Fixed output     | DALI Test   | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |
| <b>AXMW/D/2300/4K8/ED</b> | White  | ø 190     | DALI / Switchdim | DALI Test   | 2259                  | 20.5                     | 110.2            | 3K/4K/5K         | >80 |

- 3 year warranty
- See website for LDT files
- For CAD/BIM contact us
- For bespoke lengths please contact us
- See website for Technical Data Sheet

## RECESSED LED DOWNLIGHT

### Construction

- Recessed opal diffuser
- Bezel white RAL 9016
- Tridonic SMD LED
- 160mm ø cutout size

### Features

- IP54 front IP20 rear
- Dimming and emergency options
- L70 / B50 @ 50,000 hours

### Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

### Benefits

- Contemporary style
- Energy efficient solution
- European brand control gear
- Switchable CCT

### Optical Options

| Code | Description     |
|------|-----------------|
| N/A  | Opal (Standard) |

### CCT Options

| Code | Description |
|------|-------------|
| 4K8  | 4000K       |

Fitting is switchable between 3000K, 4000K and 5000K and will be supplied as 4000K as standard.

### Control Options

| Code | Description       |
|------|-------------------|
| D    | DALI              |
| S    | Switchdim control |

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

### Mounting Options

| Code | Description                                      |
|------|--|
| N/A  | Recessed (Standard)                              |
| N/A  | Surface version available see spec Axiom Surface |

### Finish Options

| Code | Description    |
|------|----------------|
| W    | White RAL 9016 |

### Emergency Options

| Code | Description                      |
|------|----------------------------------|
| /EM  | 3 hour maintained, manual test   |
| /ED  | 3 hour maintained DALI/Self Test |

For emergency version, add onto end of part number as required

### Dimensions

