


# SOMBRERO DISC LOW GLARE

## LED FEATURE PENDANT DISC



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
Suspended							
<b>SOMDSB/HX/F/0340/4K8</b>	Black	340 ø x 80	2216	17	130.4	4000K	>80
<b>SOMDSB/HX/F/0440/4K8</b>	Black	440 ø x 80	2491	18	138.4	4000K	>80
<b>SOMDSB/HX/F/0540/4K8</b>	Black	542 ø x 80	5014	36	139.3	4000K	>80
<b>SOMDSB/HX/F/0820/4K8</b>	Black	822 ø x 80	10469	65	161.1	4000K	>80
Surface							
<b>SOMDCB/HX/F/0340/4K8</b>	Black	340 ø x 80	2216	17	130.4	4000K	>80
<b>SOMDCB/HX/F/0440/4K8</b>	Black	440 ø x 80	2491	18	138.4	4000K	>80
<b>SOMDCB/HX/F/0540/4K8</b>	Black	542 ø x 80	5014	36	139.3	4000K	>80
<b>SOMDCB/HX/F/0820/4K8</b>	Black	822 ø x 80	10469	65	161.1	4000K	>80
Recessed							
<b>SOMDRB/HX/F/0340/4K8</b>	Black	350 (340) ø x 80	2216	17	130.4	4000K	>80
<b>SOMDRB/HX/F/0440/4K8</b>	Black	450 (440) ø x 80	2491	18	138.4	4000K	>80
<b>SOMDRB/HX/F/0540/4K8</b>	Black	552 (542) ø x 80	5014	36	139.3	4000K	>80
<b>SOMDRB/HX/F/0820/4K8</b>	Black	832 (822) ø x 80	10469	65	161.1	4000K	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- See website for Technical Data Sheet

REVISED : 6 November 2020 4:21 pm



# SOMBRERO DISC LOW GLARE

## LED FEATURE PENDANT DISC

### Construction

- Extruded aluminium profile
- Surface, suspended or recessed
- Clip-in diffuser
- Tridonic LED boards

### Features

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

### Applications

- Commercial and Business Areas
- Public buildings
- Retail
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

### Benefits

- Custom-finish options
- Contemporary style
- Energy efficient solution
- European control gear

### Optical Options

Code	Description
N/A	Low Glare (Standard)

### CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

### Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D'  
for SwitchDim replace 'F' with 'S'

### Mounting Options

Code	Description
N/A	Suspended
N/A	Surface
N/A	Recessed

### Finish Options

Code	Description
B	Black RAL 9005 (Standard)
W	White RAL 9016
S	Silver RAL 9006
RAL	Any RAL by request
SFX	Special effect finishes (SFX) by request. See Product Portfolio

For White finish, replace 'B' in part number with 'W' for Silver replace 'B' with 'S'. Contact us for custom RAL and SFX finish prices

### Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required

synergy.gb.net

01992 445828

sales@synergy.gb.net

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25 °C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/- 10%. Synergy reserve the right to amend or change details without prior notification.

synergy.gb.net