



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
<b>PLR/12/F/3430/4K8</b>	White	1167x62x72	3430	30	114.3	4000K	>80
<b>PLR/12/F/4500/4K8</b>	White	1167x62x72	4500	41	109.8	4000K	>80
<b>PLR/15/F/4900/4K8</b>	White	1467x62x72	4900	42	116.7	4000K	>80
<b>PLR/15/F/6600/4K8</b>	White	1467x62x72	6600	58	113.8	4000K	>80

- 5 year warranty
- See website for LDT files
- For CAD/BIM contact us
- See website for Technical Data Sheet
- For 3000K version, replace '4K8' in part number with '3K8'
- For DALI or Switchdim control, replace 'F' in part number with 'D'
- For emergency version, add onto end of part number as required:
  - /EM' = 3 hour maintained, manual test emergency pack
  - /ED' = 3 hour maintained, DALI test emergency pack

## LED BATTON

### Construction

- LED light source
- Opal diffuser

### Features

- Emergency options
- Dimmable Options

### Applications

- Offices
- Public spaces
- Hospitals
- Retail environments
- Hotels and restaurants
- Schools

### Benefits

- 5 Year warranty
- Energy saving

### Optical Options

Code	Description
N/A	Opal (Standard)

### CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

### Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D'  
for SwitchDim replace 'F' with 'S'

### Mounting Options

Code	Description
N/A	Surface Mounted

### Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required