



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
LNC/12/F/4100/4K8	White	1247x207x70	4138	38	109	4000K	>80
LNC/15/F/6200/4K8	White	1547x207x70	6185	53	117	4000K	>80

- 5 year warranty
- See website for LDT files
- For BIM models, please contact us
- See website for Technical Data Sheet

SURFACE MOUNTED LUMINAIRE

Construction

- Polycarbonate opal diffuser
- Steel body
- Polycarbonate end caps

Features

- IP44
- Microwave sensor
- Corridor function

Applications

- Commercial and Industrial
- Public and outdoor spaces
- Hospitals
- Sports areas
- Warehouses and factories
- Parking and transport terminals

Benefits

- Easy to install
- Replaces old T5 fittings
- Easy maintenance
- Easy cleaning

Optical Options

Code	Description
N/A	Opal

CCT Options

Code	Description
4K8	4000K (Standard)
3K8	3000K

For 3000K version, replace '4K8' in part number with '3K8'

Control Options

Code	Description
D	DALI
S	Switchdim control
/CF	Corridor function
/MW	Microwave sensor

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Mounting Options

Code	Description
N/A	Surface

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required. 662mm versions unavailable with emergency conversion pack