



Code	Finish	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Efficacy (lm/cw)	Colour Temp (°K)	CRI
TTR/66/F/3600/3K8	White	Nom 600x600	3450	32	107.8	3000	>80
TTR/66/F/3600/4K8	White	Nom 600x600	3600	32	112.5	4000	>80
TTR/66/F/5100/3K8	White	Nom 600x600	4850	47	103.2	3000	>80
TTR/66/F/5100/4K8	White	Nom 600x600	5100	47	108.5	4000	>80

- Part numbers are for individual luminaires.
- 5 year warranty
- See website for LDT files
- For BIM models, please contact us
- See website for Technical Data Sheet

WELLBEING LED LUMINAIRE

Construction

- Micro prismatic central diffuser
- Philips LED and driver
- Tridonic HCL tunable white version
- Wireless option

Features

- Direct / indirect
- 70,000h L70/B10
- Range of mounting options

Applications

- Offices
- Public buildings
- Healthcare
- Retail
- Leisure
- Educational

Benefits

- No visible flicker (IEEE 1789 - 2015)
- Low glare
- Highly efficient
- High output

Optical Options

Code	Description
N/A	Low glare (Standard)

CCT Options

Code	Description
4K8	4000K
3K8	3000K

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Mounting Options

Code	Description
N/A	Recessed (Standard)
TTR/PBFRAME	Plasterboard frame
TTR/SUSKIT	Suspension kit
TTR/SURFKIT	Surface body

Please specify non standard mounting option when ordering.

Emergency Options

Code	Description
/EM	3 hour maintained, manual test
/ED	3 hour maintained, DALI / Self Test

For emergency version, add onto end of part number as required

Dimensions

