

STARR

SUSPENDED OR SURFACE LUMINAIRE

CONTRACTOR RANGE



NEXT DAY
DELIVERY

PRE
WIRED

MADE IN
BRITAIN

5 YEAR
WARRANTY

TRIDONIC

Code	Finish	Diffuser	Size (mm)	Delivered Lumens (lm)	Total System Wattage (W)	Control Gear	Emergency	Colour Temp (°K)	CRI
NEXT DAY DELIVERY									
STRLIB/1/OS/F/1128/4K8	Black	Opal	1128	3151	35	Fixed Output	No	4000	>80
STRLIB/1/OS/D/1128/4K8	Black	Opal	1128	3151	35	DALI	No	4000	>80
STRLIB/1/OS/F/1688/4K8	Black	Opal	1688	4727	53	Fixed Output	No	4000	>80
STRLIB/1/OS/D/1688/4K8	Black	Opal	1688	4727	53	DALI	No	4000	>80
STRLIB/1/OS/F/2248/4K8	Black	Opal	2248	6302	70	Fixed Output	No	4000	>80
STRLIB/1/OS/D/2248/4K8	Black	Opal	2248	6302	70	DALI	No	4000	>80
2/3 WORKING DAYS DELIVERY									
STRLIB/1/OS/F/1128/4K8/E	Black	Opal	1128	3151	35	Fixed Output	Manual Test	4000	>80
STRLIB/1/OS/D/1128/4K8/E	Black	Opal	1128	3151	35	DALI	Manual Test	4000	>80
STRLIB/1/OS/F/1688/4K8/E	Black	Opal	1688	4727	53	Fixed Output	Manual Test	4000	>80
STRLIB/1/OS/D/1688/4K8/E	Black	Opal	1688	4727	53	DALI	Manual Test	4000	>80
STRLIB/1/OS/F/2248/4K8/E	Black	Opal	2248	6302	70	Fixed Output	Manual Test	4000	>80
STRLIB/1/OS/D/2248/4K8/E	Black	Opal	2248	6302	70	DALI	Manual Test	4000	>80

• Part numbers are for individual luminaires.

• 5 year warranty

• 2m suspension kit included

REVISED : 12 February 2021 3:48 pm



Construction

- Extruded aluminium profile
- Clip-in diffuser
- European brand control gear
- Made in the UK

Features

- High efficiency LED boards
- Range of length options
- Wide-beam light distribution

Applications

- Commercial and Business Areas
- Public buildings
- Housing
- Offices
- Hotels and Restaurants
- Arts and Culture spaces

Benefits

- Custom-fit options
- Contemporary style
- Energy efficient solution
- 5 Year warranty

Optical Options

Code	Description
/OS	Opal (Standard)

CCT Options


Code	Description
4K8	4000K (Standard)

Control Options

Code	Description
D	DALI
S	Switchdim control

For DALI control, replace 'F' in part number with 'D' for SwitchDim replace 'F' with 'S'

Dimensions



Mounting Options

Code	Description
P50/SUS/1.25M	Suspended 1.25M
P50/SUS/3.0M	Suspended 3M
P50/SUS/5.0M	Suspended 5M
/NA	Surface Mounted (Standard)

For suspended specify the codes as required.

Finish Options

Code	Description
B	Black RAL 9005 (Standard)

Emergency Options

Code	Description
/EM	3 hour maintained, manual test

For emergency version, add onto end of part number as required